

**8.7"** Easily Portable



**11"** Effortlessly Versatile



**14**" Large Display



As Thin As 7mm

## **Professional Features**



## Comprehensive accessory solutions for multiple scenarios.

Mobile Accessories. Ideal for mobile operations.







Make CPad your new desktop ECR with bases that are easy to install and remove.





Multiple ports integrated for functionality expansion.

Use table-side stands that are sturdy, power bank compatible, and fit various desktop settings.





Easily movable and adjustable

## Wall-Mount Accessories





8MP 13MP

## **SUNMI CPad Tech Specs**

<b>CPU</b> Octa-core, up to 2.4GHz	<b>OS</b> SUNMI OS 4.0 (Based on Android 14)	Memory 4GB RAM + 64GB ROM 8GB RAM + 128GB ROM Extended Micro SD Card Slot Up to 256GB	<b>Displays</b> 11" WUXGA, 1920*1200 Pixels, IPS Multi-Touch Capacitive Touch Screen	GMS Supported (Optional)
Buttons 1*Power button 1*Volume button	<b>Card Slots</b> Wi-Fi version: 1*MicroSD 4G version: 1*Nano SIM + 1*MicroSD	<b>eSIM</b> Supported (Optional)	Interface 2*Type-C 6*Pogo PIN at the bottom for connecting accessories 8*Pogo PIN on the back for connecting accessories	<b>Cellular</b> 4G/3G/2G
<b>Wi-Fi</b> 6GHz/5GHz/2.4GHz IEEE 802.11 ax/a/b/g/n/ac 2*2MIMO	Hyper Wi-Fi Supported (Optional)	Bluetooth Bluetooth 5.3, Support BLE	<b>Positioning</b> GPS/Glonass/Beidou/Galileo	<b>Cameras</b> 5MP FF Front Camera + AF Rear Camera 5MP FF Front Camera + AF Rear Camera
Scanner Professional 2D Scan Engine (Optional)	NFC Supported (Optional) Tap on screen Support SOFTPOS, EMVCo PCD L1 Compliant Support ISO/IEC 14443 TypeA/B, Mifare, Felica, ISO 15693 Support NFC tag	Fingerprint Supported (Optional)	Audio 2*Speaker 2*Microphone	LED Indicator Supported
<b>Battery</b> Non-removable Lithium Polymer Battery 4.45V/8000mAh	<b>Sensors</b> Gravity sensor Light sensor Proximity sensor Geomagnetism (Optional)	Adapter Input: 100V-240V AC Output: 9V2A/5V2A DC	Dimensions(L*W*H) 256.1*168.2*10.1 mm	Net Weight <sup>526g</sup>
<b>Protection</b> IP54	<b>Environment</b> Operating Temperature: -10°C to 50°C Storage Temperature: -20°C to 60°C Operating Humidity:	Accessories (Optional) Desktop Base Printing Base Multi-Function Pivoting Base Table-Side Fixed Stand Table-Side Stand	Hand Strap and Mount Protective Case Mount Adapter 4-Slot Charging Base Desktop Stand	

\*The 8.7° and 11° PADs are not yet available, and their accessories are not fully launched. For specific release dates, please contact the sales reps of your region \*This product description is based on the current information available at the time of launch. Due to product upgrades or other reasons, the content may change. The company reserves the right

External Barcode Scanner

Shoulder Strap

5% to 95% non-condensing