Smart Mobile Terminal

SUNMI M3

Now, empower your entire restaurant operations.

Powered by		Compatible with
Android Enterprise	Google Mobile Services	

Enhanced Experience. Seamless ordering and payment experience.

Experience the 6.75" HD display that offers ultimate ordering experience. Enjoy swift, hassle-free checkout with NFC-enabled SoftPOS payments.

• Enhanced Performance. Smooth operations during peak times.

Powered by an 8-core 2.2GHz processor, it delivers smooth performance without lag. The 5000mAh battery and intelligent algorithm ensure all-day reliability.

• Enhanced design. A device built for extended use.

With a sleek metallic finish and ergonomic curved design, it fits perfectly in your hand for comfortable use.

• Enhanced Protections. Durability designed for harsh environments.

With an IP65 rating for dust and water resistance, it withstands real-world challenges and also survives drops from 1.5 meters onto concrete.

8x * Performance Boost

Octa-Core

CPU

2.2GHz Max Clock Speed

400,000+





6.75" HD+ Screen Ultimate ordering experience at your fingertips.

Over 10x the Range of Other Wi-Fi

SUNMI Hyper Wi Wide coverage, strong penetration, high stability, and intelligent switching for seamless communication.

67% Increase In Battery Capacity

5000mAh Supports over 800 charging cycles.



SUNMI M3 Applications



Queue Management

Mobile Ordering

Payment Processing

Single Charging Base 4-Slot Charging Base 4-Slot Battery Charger

Meet accessories that boost your efficiency.



SUNMI M3 Tech Specs

CPU OS Memory Displays GMS 3GB RAM + 32GB ROM 4GB RAM + 64GB ROM SUNMI OS 4.0 (Based on 6.75" HD+, 720*1600 Pixels Octa-core, up to 2.2GHz Android 14) Up to 256GB Touch Screen **Card Slots** eSIM Wi-Fi **Buttons** Interface 1*Power button 1*Custom button 1*Micro SD 1*PSAM (Optional) 1*Type-C 6*Pogo PIN at the bottom for 5GHz/2.4GHz IEEE 802.11 a/b/g/n/ac Supported (Optional) connecting accessories Hyper Wi-Fi Bluetooth Positioning Cameras NFC 2MP FF Front Camera + 2MP FF Rear Camera GPS/Glonass/Beidou/Galileo Supported (Optional): Tap on screen Support SOFTPOS, EMVCo PCD L1 Certified Support ISO/IEC 14443 TypeA/B, Mifare, Felica, ISO15693 LED Indicator Audio Battery Adapter Sensors 1*Speaker 2*Microphone Input: 100V-240V AC Supported Removable Lithium Light sensor Polymer Battery 4.4V/5000mAh Proximity sensor Output: 5V2A DC Dimensions(L*W*H) Net Weight Protection Environment Accessories IP65 1.5m Drop Test (Concrete floor) Operating Temperature: -20°C to 55°C 175*79*15 mm Tempered Glass Screen Protector Protective Case Hand Strap Storage Temperature: -40°C to 70°C Operating Humidity: 5% to 95% non-condensing Lanyard Shoulder Starp

*This product description is based on the current information available at the time of launch. Due to product upgrades or other reasons, the content may change. The company reserves the right to modify the product and content without prior notice